

Endless webbing sling

- According to JB/T8521.1.2007 and EU EN1492-1:2000+A1:2008 standard.
- The webbing sling of polyamide, polyester and polypropylene can be provided according to different service environments.
- Suitable temperature: polyester, polyamide -40°C~100°C , polypropylene-40°C~80°C.
- Wear-resistant sheath sewn on the ring.
- Safety factor 6:1 or 7:1



TYPE W03 Standard Type								
Model	Color	WLL (kg)	Thickness (mm)	Width 6:1 (mm)	Width 7:1 (mm)	Length (m)	Weight 6:1 (kg/m)	Weight 7:1 (kg/m)
W03-01		1000	4	25	30	0.5~100	0.18	0.2
W03-02		2000	4	50	60	1~100	0.39	0.42
W03-03		3000	4	75	90	1~100	0.62	0.65
W03-04		4000	4	100	120	1.5~100	0.73	0.9
W03-05		5000	4	125	150	1.5~100	0.96	1.14
W03-06		6000	4	150	180	1.5~100	1.12	1.33
W03-08		8000	4	200	240	2.0~100	1.65	1.85
W03-10		10000	4	250	300	2.0~100	2.05	2.32
W03-12		12000	4	300	300	2.0~100	2.34	2.94

TYPE W04 Widening Type								
Model	Color	WLL (kg)	Thickness (mm)	Width 6:1 (mm)	Width 7:1 (mm)	Length (m)	Weight 6:1 (kg/m)	Weight 7:1 (kg/m)
W04-02		2000	7.5	25	30	0.5~100	0.44	0.5
W04-04		4000	7.5	50	60	1~100	0.82	0.9
W04-06		6000	7.5	75	90	1~100	1.32	1.42
W04-08		8000	7.5	100	120	1.5~100	1.76	2
W04-10		10000	7.5	125	150	1.5~100	2.24	2.62
W04-12		12000	7.5	150	180	1.5~100	2.68	2.92
W04-16		16000	7.5	200	240	2.0~100	3.64	3.78

W04-20		20000	7.5	250	300	2.0~100	4.7	4.92
W04-24		24000	7.5	300	300	2.0~100	5.18	5.54

