

Eye-Eye round sling

- According to JB/T8521.1.2007 and EU EN1492-2:2000+A1:2008 standard.
- The round sling of polyamide, polyester and polypropylene can be provided according to different service environments.
- Suitable temperature: polyester, polyamide -40°C~100°C , polypropylene-40°C~80°C.
- Wear-resistant sheath sewn on the ring.
- Safety factor 6:1 or 7:1



Standard Type

Model	Color	WLL(kg)	Thickness (mm)	Width(mm)	Length(m)	Weight 6:1 (kg/m)	Weight 7:1 (kg/m)
R02-01		1000	15	50	1.5~80	0.3	0.33
R02-02		2000	16	60	1.5~80	0.44	0.47
R02-03		3000	18	70	1.5~80	0.65	0.68
R02-04		4000	20	80	1.5~80	0.83	0.85
R02-05		5000	25	90	1.5~80	1.01	1.06
R02-06		6000	27	90	2~80	1.19	1.28
R02-08		8000	28	100	2~80	1.5	1.59
R02-10		10000	29	110	2~80	1.95	2.1
R02-12		12000	30	125	2~80	2.46	2.6
R02-15		15000	31	150	2~80	2.97	3.16
R02-20		20000	32	180	2.5~80	4.66	4.89
R02-25		25000	34	200	2.5~80	5.84	6.15
R02-30		30000	68	220	2.5~80	9.23	9.51
R02-40		40000	75	250	2.5~80	12.1	12.45
R02-50		50000	86	270	2.5~80	14.1	14.4
R02-60		60000	126	280	4~80	17.3	18
R02-80		80000	138	300	4~80	22.2	23.1
R02-100		100000	152	320	4~80	26	27.1
R02-200		200000	230	460	5~80	55	65.9
R02-300		300000	310	535	5~80	79	80.9
R02-400		400000	380	680	5~80	98.4	100.2
R02-500		500000	410	760	8~80	121.2	123.5
R02-600		600000	460	830	8~80	145	147.5
R02-700		700000	498	880	8~80	168	170.9

High strength Dinima type

- The Ultra high molecular weight polyethylene (Dinima) was used as raw material, strength is 3-4 times of

high tenacity polyester.

- The specific gravity is 0.97g/cm³ (lighter than water and floating on the water surface).
- The fiber is superior to other synthetic fibers in UV resistance, impact resistance, acid resistance, corrosion resistance and wear resistance.
- Low temperature performance is well Used in -125 ~ 80 degrees centigrade environment, weight is ordinary sling 1/4, diameter is ordinary sling 1/2.
- It has the characteristics of small size, light weight, soft, safe, small elongation, ultraviolet radiation resistance, wear resistance, impact resistance, corrosion resistance, non conductive, antistatic and long service life.

Model	Color	WLL(kg)	Thickness (mm)	Width(mm)	Length(m)	Weight 6:1 (kg/m)
RH02-01		1000	12	24	1.5~80	0.13
RH02-02		2000	18	26	1.5~80	0.21
RH02-03		3000	22	35	1.5~80	0.25
RH02-04		4000	25	45	1.5~80	0.27
RH02-05		5000	30	50	1.5~80	0.29
RH02-06		6000	32	55	2~80	0.33
RH02-08		8000	35	65	2~80	0.53
RH02-10		10000	38	70	3~80	0.74
RH02-12		12000	40	75	3~80	0.97
RH02-15		15000	45	80	3~80	1.27
RH02-20		20000	45	95	4~80	1.73
RH02-25		25000	48	110	4~80	2.17
RH02-30		30000	60	125	4~80	2.6
RH02-40		40000	65	130	4~80	3.47
RH02-50		50000	70	140	4~80	4.3
RH02-60		60000	72	150	4~80	5.2
RH02-80		80000	75	155	4~80	6.93
RH02-100		100000	80	160	4~80	8.3

