

Fire Proof Lifting Sling

- According to JB/T8521.2-2007.
- Suitable for high temperature environment, temperature range: -40°C~180°C.
- Combustion does not produce toxic gases .
- Adopt imported Swiss loom and German dyeing and finishing machine.
- Safety factor 6:1 and 7:1.

Fire Proof Endless Sling



Model	Color	WLL (kg)	Thickness (mm)	Width (m)	Length Range (m)	Weight 6:1 (kg/m)
RK01-01		1000	4	30	1.5~80	0.28
RK01-02		2000	5	40	1.5~80	0.42
RK01-03		3000	6	50	1.5~80	0.5
RK01-04		4000	7	60	1.5~80	0.56
RK01-05		5000	8	70	1.5~80	0.6
RK01-06		6000	9	75	2~80	0.7
RK01-08		8000	11	80	2~80	0.8
RK01-10		10000	13	90	2~80	1.5
RK01-12		12000	14	100	3~80	2.24
RK01-15		15000	16	110	3~80	2.66
RK01-20		20000	18	125	3~80	3.64

Fire Proof Eye-Eye webbing Sling



Model	Color	WLL (kg)	Thickness (mm)	Width (m)	Length Range (m)	Weight 6:1 (kg/m)
RK02-01		1000	10	40	1.5~80	0.3
RK02-02		2000	11	50	1.5~80	0.45
RK02-03		3000	12	60	1.5~80	0.6
RK02-04		4000	14	70	1.5~80	0.9
RK02-05		5000	18	75	1.5~80	1.03
RK02-06		6000	19	80	2~80	1.19
RK02-08		8000	20	90	2~80	1.54

RK02-10		10000	21	100	2~80	2.1
RK02-12		12000	22	110	3~80	2.38
RK02-15		15000	23	125	3~80	2.8
RK02-20		20000	24	150	3~80	3.9