

## Stainless Steel Turnbuckle

- Mainly used for the tightening of goods and adjust the tightness.
- Safety factor 4:1
- Only for linear tension or linear force.
- Material: 304, 304L, 316, 316L, 304 non magnetic .

### Eye&HookType



IETM No.	Size(mm)					Adjustable Length	WLL Kg	Self Weight Kg
	C	D	S	L	L1			
M4	9.3	5	7.5	60	107	39	25	0.035
M5	9.7	5	7.5	73	124	59	40	0.039
M6	10.5	6	9.6	91	150	64	100	0.077
M8	12.5	8	9.6	122.8	192	96	200	0.14
M10	15	10	11.3	150	240	115	300	0.26
M12	17.5	12	18.4	197	303	163	500	0.48
M16	26.5	16	21.8	248	385	193	800	1
M20	30.1	20	22.1	299	465	232	1200	1.96
M24	24.9	24	23.7	356	531	269	2500	3.39

### Jaw&Jaw Type



IETM No.	Size(mm)					WLL	Self Weight
	A	B	D	L2	L1	Kg	Kg
M5	9	81	5	122	180	40	0.048
M6	9	90	5	137	210	100	0.084
M8	10	110	6	155	250	200	0.13
M10	11	120	8	178	275	300	0.21
M12	16	150	10	237	350	500	0.36
M16	15	190	14	280	450	800	0.84
M20	24	222	15	350	525	1200	1.49